

e.lift 1500 to 2200 lbs

TEMPORARY PERSONNEL LIFTING WIRE ROPE ELECTRIC HOIST

e.lift NEO is a versatile personnel lifting hoist for use with suspended platforms and cradles

Load capacity of 1500 lbs (680 kg) to 2200 lbs (1000 kg)



VERSATILITY

- ✓ Can be used on a variety of job sites
- ✓ Unlimited working height



SAFETY

- ✓ Electronic Overload switch - N.E.O System
Display indicates load
- ✓ Obstacle switch during descent
- ✓ Overspeed safety device - Securichute
- ✓ Easy & fast maintenance



✓ N.E.O System

- Functions:
- exact weighing of the lifted load
 - load limiter
 - time meter



COMFORT

- ✓ Hour meter - N.E.O System
- ✓ Voltage indicator
- ✓ Compact & light
- ✓ Easy to transport: wheels (optional)
- ✓ Carrying handles

TECHNICAL FEATURES	527 A	527 C
Load Capacity (lbs/kg)	2200/1000	1500/680
Operating speed	30ft/min (9m/min - 0.15m/s)	30ft/min (9m/min - 0.15m/s)
Dimensions (in/mm)	31.1"/16.1"/11.5" (789x408x291 mm)	31.1"/16.1"/11.5" (789x408x291 mm)
Voltage	208 V -- 3 ~ 60Hz	208 V -- 3 ~ 60Hz
Motor Power	2.5 HP / 1.85 kW	2.5 HP / 1.85 kW
Wire rope diameter	3/8" (9.5 mm) - 5x19 or 5x26	3/8" (9.5 mm) - 5x19 or 5x26
Temperature for use	14°F / 131°F (-10°C/+55°C)	14°F / 131°F (-10°C/+55°C)
Weight (lbs/kg)	160/73	160/73
Load limiter	Yes, adjustable	Yes, adjustable



Distributed by:
BEE ACCESS, LLC | 2145 Indian Road West Palm Beach, FL 33409
T. 1-561-616-9003 | E. sales@beeaccess.com
www.beeaccess.com



MANUFACTURER OF HEIGHT ACCESS FOR 95 YEARS