



FS700-25GA through FS700-100GA

PRO Vertical Lifeline Assembly : Snap Hook, Rope Grab

FEATURES :

- 5/8" Polyester rope
- 1 Snap hook
- Non-removable rope grab with dual-cam, and quick locking
- Rope tensile strength: 7,500 lbs.
- Hook gate rating: 3,600 lbs.
- Hook minimum breaking strength: 5,000 lbs.

FALL ARREST POINT(S) :

- 1 Snap hook

ITEM WEIGHT :

- Weight varies by length



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	N/A
OSHA	1926.502, 1910.66, 1910.140

Size(s)		
FS700-25GA	25 Feet (8 m)	4 lbs. (2 kg)
FS700-50GA	50 Feet (15 m)	7 lbs. (3 kg)
FS700-75GA	75 Feet (23 m)	10 lbs. (5 kg)
FS700-100GA	100 Feet (31 m)	12 lbs. (5 kg)

COMPONENT	MATERIAL SPECIFICATION
Rope	Polyester
Snap hook	Zinc plated alloy steel
Rope Grab	Zinc plated alloy Steel